

600 SLX

Material Safety Data Sheet

5700 N. Portland, Suite 301 / Oklahoma City, OK 73112 / Phone: (405) 947-0765 / Fax: (405) 947-0768

SECTION 1 - PRODUCT INFORMATION

TRADE NAME: Slurry 600 SLX & 6000 series
SYNONYM: NA
CHEMICAL FAMILY: Watergel Slurry Explosive
FORMULA: Mixture
CAS NUMBER: None
UN/NA NUMBER: UN0332
DOT HAZARD CLASS: Explosive, Blasting,
Type E, Class 1.5 D

SECTION 2 - HEALTH ALERT

DANGER - If misused or disposed of improperly, material could explode and cause death or serious injury.
DO NOT HANDLE WHEN IN DOUBT!!
See section VIII - Personal Protection
CHEM-TEL, INC. (800) 255-3924.

SECTION 3 - HEALTH HAZARD INFORMATION

EYE: May cause moderate irritation.

SKIN: May cause moderate irritation characterized by redness and/or rash.

INHALATION: Inhalation of decomposed products may irritate the respiratory tract. Prolonged exposure to these fumes may result in respiratory difficulties (shortness of breath, etc.) and possibly more severe toxic effects.

INGESTION: Swallowing large quantities may cause toxicity characterized by dizziness, bluish skin coloration, methemoglobinemia, unconsciousness, abdominal spasms, nausea, and pain.

SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush with large amounts of water. Seek medical aid.

SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly with soap and water.

INHALATION: Remove from exposure. If breathing stops or is difficult, administer artificial respiration or oxygen. Seek medical aid.

INGESTION: Give 8-16 oz. of milk or water. Induce vomiting. Seek medical aid.

SECTION 5 - RECOMMENDED OCCUPATIONAL EXPOSURE LIMIT/ HAZARDOUS INGREDIENTS

EXPOSURE LIMIT (PRODUCT): None required for product

<u>HAZARDOUS INGREDIENTS:</u>	<u>PERCENT</u>	<u>EXPOSURE LIMIT</u>	<u>PPM</u>	<u>MG/M3</u>
Ammonium Nitrate	< 80%	NONE		
Sodium Perchlorate	<5%	NONE		
Nitric Acid*	<5%	ACGIH-TLV		2
Hexamine*	<10%	None established		

*React to form Hexamine dinitrate.

NOTE: All ingredients are present in a gelled slurry matrix and individual hazard may not be present in this formulation.

SECTION 6 - REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: Heat (confinement); Stacking (burning).

INCOMPATIBILITY: Can react violently or explode, with reducing agents and organic materials.

HAZARDOUS REACTION / DECOMPOSITION PRODUCTS: At high temperatures, especially >374 F, may emit severe toxic fumes of nitrogen oxides.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: Not applicable.

SECTION 7 - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT & METHOD: NA **AUTO IGNITION TEMPERATURE:** Explodes

FLAMMABLE LIMITS (% BY VOLUME/AIR): LOWER: NA UPPER: NA

EXTINGUISHING MEDIA: Water

FIRE-FIGHTING PROCEDURES: When explosive is burning, EVACUATE AREA. Avoid breathing vapor

FIRE & EXPLOSION HAZARDS: Dangerous when exposed to heat or flame. Can support combustion of other materials involved in a fire and is capable of undergoing detonation if heated to high temperatures, especially under confinement including being piled on itself in a burning fire. When heated to decomposition, highly toxic fumes may be emitted. Do not return to area of explosion until smoke and fumes have dissipated.

600 SLX

Material Safety Data Sheet

SECTION 8 - PERSONAL PROTECTION INFORMATION

EYE PROTECTION: Safety goggles approved for the handling of explosives materials.

SKIN PROTECTION: Neoprene, natural rubber, polyethylene or polyvinyl chloride gloves. Use barrier creams, hand protection and protective clothing.

RESPIRATORY PROTECTION: Not normally required. Mechanical filter or supplied air type respirator as required for concentrations exceeding the occupational exposure limit.

VENTILATION: Maintain adequate ventilation. Use local exhaust if needed.

SECTION 9 - PERSONAL HANDLING INSTRUCTIONS

HANDLING: Explosives should not be abandoned at any location for any reason. Do not handle during electrical storms.

STORAGE: Store in a cool, dry, well-ventilated area remote from operations. Storage area should be of non-combustible construction. Organic materials, flammable substances and finely divided metals should be stored separately. Flames, smoking and unauthorized personnel are prohibited where this product is used or stored. Protect against physical damage, static electricity and lightning.

WARNING: Use of this product by persons lacking adequate training, experience and supervision may result in death or serious injury. Obey all Federal, State, and local laws / regulations applicable to transportation, storage, handling, and use of explosives.

DISTANCE: Always stay from area of explosion or disposal sites. Stay behind suitable barriers.

SECTION 10 - SPILL & LEAK PROCEDURES

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED (IN ADDITION, SEE SECTION 8): Isolate area. Eliminate ALL sources of ignition. Avoid skin contact. Scrape up. Remove soiled clothing.

WASTE DISPOSAL - USE APPROPRIATE METHOD(S): Disposal of unexploded or deteriorated explosives material can be hazardous. Expert assistance is positively recommended in destroying explosives. Accidents can be prevented by thorough planning and handling in accordance with approved methods. Consult your supervisor, or the nearest SEC Regional Office for assistance. If improperly disposed of, material could explode and cause death or serious injury.

In all cases, follow facility emergency response procedures. Contact Facility Environmental Manager for assistance. Report any discharge of oil or hazardous substance that may enter surface waters to the National Response Center (800) 424 - 8802.

Observe all applicable local, state, and federal environmental spill and water quality regulations.

SECTION 11 - PHYSICAL DATA

BOILING POINT: NA **BULK DENSITY:** 1.15 g/cc **MELTING POINT:** NA
%VOLATILE BY VOLUME: 0 **VAPOR PRESSURE:** NA **EVAPORATION RATE (ETHER=1):** 0
VAPOR DENSITY (AIR=1): NA **VISCOSITY:** NA
SOLUBILITY IN WATER: Negligible with short term exposure **APPEARANCE/ ODOR:** Gel

SECTION 12 - COMMENTS

This product is classified as a Blasting Agent and need not be stored in a high explosive magazine, except where required by local regulations, as long as it is completely separate from any high explosives. Storage should be in a well constructed, well ventilated, dry structure located to conform with local, state, and federal regulations. The area surrounding an explosive magazine must be kept clear of combustible materials for a distance of 50 feet. Magazine floors and containers must be properly cleaned.

Normal operating conditions are assumed unless otherwise stated. If any given information is not clear or does not apply to your situation, STOP, store the material suitably, and seek correct help from your supervisors, Institute of Makers of Explosives or Slurry Explosive Corporation. Disposal sites must be clear of people at the time of disposal.

NOTICE: The data and recommendations presented herein are based upon data which are considered to be accurate. However, SEC makes no guarantee or warranty, either expressed or implied, of the accuracy or completeness of these data and recommendations.

For more detailed information on the hazards of this product, contact the Regulatory Compliance Department at the address below:

Slurry Explosive Corporation
P. O. Box 348
Columbus, Kansas 66725
(620) 597-2552